



Spring-type straight pins - Slotted, heavy duty
Goupilles élastiques - Serie epaisse

Pasadores elásticos

d1 (nom)	8	10	12	13	14	16	18	20
d1 (min)	8,5	10,5	12,5	13,5	14,4	16,5	18,5	20,5
	8,8	10,8	12,8	13,8	14,8	16,8	18,9	20,9
d2=	5,5	6,5	7,5	8,5	8,5	10,5	11,5	12,5
s	1,5	2	2,5	2,5	3	3	3,5	4
a (min)	2	2	2	2	2	2	2	3
Carga cizalladura de dos hilos (Kn)	42,76	70,16	104,1	115,1	144,7	171	222,5	280,6
Shear strength double min. (kN)								

L\d: Peso/Weight 1000 ud. kg

10	2,240	3,690	5,550	6,180	7,800	9,190	12,90	15,30
12	2,660	4,430	6,660	7,420	9,350	11,00	14,50	18,40
14	3,130	5,170	7,780	8,660	10,90	12,90	16,90	21,40
16	3,580	5,900	8,890	9,900	12,50	14,70	19,30	24,50
18	4,030	6,640	10,00	11,10	14,00	16,50	21,80	27,50
20	4,480	7,380	11,10	12,40	15,60	18,40	24,20	30,60
22	4,920	8,120	12,20	13,60	17,10	20,20	26,60	33,60
24	5,370	8,860	13,30	14,80	18,70	22,00	29,00	36,70
26	5,820	9,590	14,40	16,10	20,30	23,90	31,40	39,80
28	6,260	10,30	15,60	17,30	21,80	25,70	33,80	42,80
30	6,710	11,10	16,70	18,50	23,40	27,60	36,30	45,90
32	7,160	11,80	17,80	19,80	24,90	29,40	38,70	48,90
36	8,060	13,30	20,00	22,30	28,10	33,10	43,50	55,10
40	8,950	14,80	22,20	24,70	31,20	36,70	48,40	61,20
45	10,10	16,60	25,00	27,80	35,10	41,30	54,40	68,80
50	11,20	18,40	27,80	30,90	39,00	45,90	60,40	76,50
55	12,30	20,30	30,50	34,00	42,90	50,50	66,50	84,10
60	13,40	22,10	33,30	37,10	46,80	55,10	72,50	91,80
65	14,50	24,00	36,10	40,20	50,10	59,70	78,60	99,40
70	15,70	25,80	38,90	43,30	54,60	64,30	84,60	107,00
75	16,80	27,70	41,70	46,40	58,50	68,90	90,70	115,00
90	18,00	29,50	44,40	49,50	62,40	73,50	96,70	122,00
85	19,00	31,40	47,20	52,50	66,30	78,10	103,00	130,00
90	20,10	33,20	50,00	55,60	70,20	82,70	109,00	138,00
95	21,30	35,00	52,80	58,70	74,10	87,30	115,00	145,00
100	22,40	36,90	55,50	61,80	77,90	91,90	121,00	153,00
120	26,80	44,30	66,60	74,20	93,50	110,00	145,00	184,00
140		51,70	77,80	85,50	109,00	129,00	169,00	214,00
160		59,00	88,90	98,90	125,00	147,00	193,00	245,00
180			100,00	111,00	140,00	165,00	218,00	275,00
200					155,00	184,00	241,00	306,00

CALIDADES/GRADES:

ST	FST	ST2(HRC:60±2) Templado/Heat treated	A2	A4
----	-----	-------------------------------------	----	----