



Cross recessed pan head tapping screws
Vis à tôle à tête cylindrique bombée large à empreinte cruciforme

Tornillos autoroscantes de cabeza cilíndrica abombada con hueco cruciforme

d	ST2,9	ST3,5	ST3,9	ST4,2	ST4,8	ST5,5	ST6,3
P	1,1	1,3	1,3	1,4	1,6	1,8	1,8
dk	5,6	6,9	7,5	8,2	9,5	10,8	12,5
k	2,2	2,6	2,8	3,05	3,55	3,95	4,55
Nr. Phillips (H)	1	2	2	2	2	3	3
Nr. ISO	4	6	7	8	10	12	14

L\d: **Peso/Weight 1000 ud. kg**

6,5	0,400	0,610	0,830				
9,5	0,510	0,790	1,050	1,220	1,850	2,800	
13	0,630	0,970	1,270	1,460	2,200	3,200	3,900
16	0,740	1,120	1,460	1,670	2,500	3,600	4,440
19	0,850	1,270	1,650	1,880	2,800	4,000	4,980
22	0,960	1,420	1,840	2,100	3,100	4,380	5,520
25	1,070	1,570	2,030	2,300	3,400	4,760	6,060
32	1,324	1,720	2,230	2,800	4,100	5,670	7,320
38	1,870	2,450	3,300	4,700	6,450	8,400	
45	2,660	3,800	5,300	7,250	9,480		
50	4,100	5,900	8,050	10,56			

CALIDADES/GRADES:

ST	ST Acero Cementado/Case hardened	A2	A4
----	----------------------------------	----	----