



Cross recessed flat countersunk head tapping screws
 Vis à tête fraisée à empreinte cruciforme

Tornillos autoroscantes de cabeza avellanada con hueco cruciforme

d	ST2,9	ST3,5	(ST3,9)	ST4,2	ST4,8	ST5,5	ST6,3
P	1,1	1,3	1,3	1,4	1,6	1,8	1,8
dk	5,5	6,8	7,5	8,1	9,5	10,8	12,4
k	1,7	2,1	2,3	2,5	3	3,4	3,8
Nr. Phillips (H)	1	2	2	2	2	3	3
Nr. ISO	4	6	7	8	10	12	14

L\d: Peso/Weight 1000 ud. kg

6,5	0,242						
9,5	0,350	0,548	0,658	0,775	1,100		
13	0,476	0,722	0,880	1,020	1,450	2,110	2,530
16	0,584	0,871	1,070	1,230	1,750	2,490	3,070
19	0,692	1,020	1,260	1,440	2,050	2,870	3,610
22		1,170	1,450	1,650	2,350	3,260	4,150
25		1,320	1,640	1,860	2,650	3,650	4,690
32				2,350	3,350	4,560	5,950
38					3,500	5,340	7,030
45					3,650	6,140	8,110
50					4,300	7,040	9,200

CALIDADES/GRADES:

ST ST Acero Cementado/Case hardened A2 A4