



Slotted countersunk head screws
 Vis à tête fraisée avec rainure

Tornillos de cabeza avellanada ranurada

d	M3	M4	M5	M6	M8	M10
P	0,5	0,7	0,8	1	1,25	1,5
dk	5,6	7,5	9,2	11	14,5	18
k (max)	1,65	2,2	2,5	3	4	5
n	0,8	1	1,2	1,6	2	2,5

L\d: Peso/Weight 1000 ud. kg

4	0,291					
5	0,335	0,676				
6	0,379	0,754	1,210			
8	0,467	0,900	1,450	2,190		
10	0,555	1,060	1,700	2,540	5,030	
12	0,643	1,220	1,950	2,890	5,670	9,590
16	0,820	1,530	2,190	3,250	6,300	10,60
20	0,996	1,840	2,440	3,610	6,940	11,60
25	1,220	2,220	2,940	4,310	8,210	13,60
30	1,440	2,610	3,180	4,660	8,840	14,60
35		2,990	3,550	5,190	9,790	16,10
40		3,360	4,160	6,080	11,40	18,60
45			4,760	6,960	13,00	21,10
50			5,390	7,840	14,60	23,60
55			6,020	8,730	16,20	26,10
60			6,650	9,610	17,80	28,60
70					19,40	31,10
80						33,70

CALIDADES/GRADES:

4.6 4.8 5.6 5.8 6.8 8.8 10.9 12.9 A2 A4