



Hexagon socket button head screws  
 Vis à métaux à tête cylindrique bombée plate à six pans creux

### Tornillos de cabeza abombada con hueco hexagonal

| d               | M3   | M4  | M5   | M6   | M8   | M10  | M12  | M16 |
|-----------------|------|-----|------|------|------|------|------|-----|
| <b>P</b>        | 0,5  | 0,7 | 0,8  | 1    | 1,25 | 1,5  | 1,75 | 2   |
| <b>dk (max)</b> | 5,7  | 7,6 | 9,5  | 10,5 | 14   | 17,5 | 21   | 28  |
| <b>k (max)</b>  | 1,65 | 2,2 | 2,75 | 3,3  | 4,4  | 5,5  | 6,6  | 8,8 |
| <b>s</b>        | 2    | 2,5 | 3    | 4    | 5    | 6    | 8    | 10  |

| L\d: |   |   |   |   |   |   |   |   |   |
|------|---|---|---|---|---|---|---|---|---|
| 6    | X | X | X | X |   |   |   |   |   |
| 8    | X | X | X | X | X |   |   |   |   |
| 10   | X | X | X | X | X |   |   |   |   |
| 12   | X | X | X | X | X | X |   |   |   |
| 16   | X | X | X | X | X | X | X |   |   |
| 20   | X | X | X | X | X | X | X |   |   |
| 25   | X | X | X | X | X | X | X |   |   |
| 30   | X | X | X | X | X | X | X |   | X |
| 35   |   | X | X | X | X | X | X | X | X |
| 40   |   | X | X | X | X | X | X | X | X |
| 45   |   |   | X | X | X | X | X | X | X |
| 50   |   |   | X | X | X | X | X |   |   |
| 55   |   |   |   | X | X | X | X |   |   |
| 60   |   | X | X | X | X | X | X | X | X |
| 70   |   |   | X | X | X | X | X | X | X |
| 80   |   |   |   |   | X | X | X | X | X |
| 90   |   |   |   |   | X | X | X |   |   |
| 100  |   |   |   |   | X | X | X |   |   |
| 110  |   |   |   |   |   |   | X |   |   |
| 120  |   |   |   |   |   |   | X |   |   |

#### CALIDADES/GRADES:

|     |     |     |     |     |     |      |      |    |    |
|-----|-----|-----|-----|-----|-----|------|------|----|----|
| 4.6 | 4.8 | 5.6 | 5.8 | 6.8 | 8.8 | 10.9 | 12.9 | A2 | A4 |
|-----|-----|-----|-----|-----|-----|------|------|----|----|