



Hexagon socket set screws with dog point
 Vis sans tête à six pans creux et pivot

Tornillos sin cabeza con hueco hexagonal y pivote

d	M3	M4	M5	M6	M8	M10	M12	M16	M20	M24
P	0,5	0,7	0,8	1	1,25	1,5	1,75	2	2,5	3
dp (max)	2	2,5	3,5	4	5,5	7	8,5	12	15	18
s	1,5	2	2,5	3	4	5	6	8	10	12
z corto (min)	0,75	1	1,25	1,5	2	2,5	3	4	5	6
short (max)	1	1,25	1,5	1,75	2,25	2,75	3,25	4,3	5,3	6,3
z largo (min)	1,5	2	2,5	3	4	5	6	8	10	12
large (max)	1,75	2,25	2,75	3,25	4,3	5,3	6,3	8,36	10,36	12,43

L\d: Peso/Weight 1000 ud. kg

5	0,163									
6	0,186	0,292								
8	0,276	0,442	0,708	1,020						
10	0,366	0,592	0,948	1,290	2,280					
12	0,456	0,742	1,190	1,630	2,680	4,410				
16	0,636	1,040	1,670	2,340	3,940	6,050	8,910			
20	0,816	1,340	2,150	3,040	5,200	8,020	11,00	20,10		
25			2,750	3,920	6,790	10,50	14,60	25,10	38,90	
30				4,800	8,380	13,00	18,20	31,90	45,50	67,70
35				5,680	9,970	15,50	21,80	38,20	55,80	78,40
40					11,60	18,00	25,40	44,90	66,10	93,40
45									76,40	108,00
50									86,70	123,00
55										138,00
60										153,00

z Corto/Short: Para las medidas sobre línea quebrada / For sizes above line

z Largo/Large: Para medidas bajo línea quebrada / For sizes below line

CALIDADES/GRADES:

45H

A2

A4