



Pozidrive countersunk head screws for chipboard
 Vis pour agglomérée à tête fraisée, pozidrive

Tornillos rosca aglomerado, cabeza avellanada, pozidrive

d	2,4	3	3,5	4	4,5	5	6
dk	4,8	6	7	8	9	10	12
k	1,7	1,9	2,3	2,6	2,9	3,2	3,9
Nr. Pozidrive (z)	1	1	2	2	2	2	3

L\d: Peso/Weight 1000 ud. kg							
8	0,216	0,312					
10	0,259	0,372	0,604	0,789			
12	0,302	0,432	0,696	0,914	1,180		
16	0,387	0,552	0,881	1,170	1,490	1,850	2,310
20	0,484	0,672	1,060	1,430	1,790	2,220	2,780
25		0,822	1,300	1,730	2,170	2,710	3,370
30		0,972	1,540	2,040	2,550	3,190	4,000
35			1,770	2,350	2,940	3,680	4,550
40			2,010	2,660	3,320	4,170	5,140
45			2,260	2,980	3,660	4,650	5,730
50				3,290	4,050	5,140	6,320
60				3,910	4,810	6,110	7,540
70							8,720
80							9,900

CALIDADES/GRADES:

ST	ST Acero Cementado/Case hardened	A2	A4
----	----------------------------------	----	----